Ultra-High Pressure Hoses & Couplers

- Hose Reel and Stand: Stainless steel stand with 1500 bar hoses from 30 upto 270 metres lengths
- · All hose reels are built up with multiple 30 metres length hoses
- Wide offering of hoses and system components to complete your tensioning system
- · Can be used for subsea fastening systems
- Hoses can be inter-connected in multi-tool set-ups using nipples, couplers, T-pieces and Y-Pipe assemblies.

1500 BAR HOSE REEL & STANDS			
Model Number		Stainless Steel Hose Reels with Stand (Hose with Female Half BR150 and Male Half BH150 couplers)	
HT15000RS		Reel & Stand Assembly, No Fittings	
HT15000HRS		Hose Reel & Stand, No Hose	
HT15100HRS		Hose Reel & Stand, with 30 m hose	
HT15200HRS		Hose Reel & Stand, with 60 m hose	
HT15300HRS		Hose Reel & Stand, with 90 m hose	
HT15400HRS		Hose Reel & Stand, with 120 m hose	
HT15500HRS	ANDIX	Hose Reel & Stand, with 150 m hose	
HT15600HRS	A000	Hose Reel & Stand, with 180 m hose	
HT15700HRS	1	Hose Reel & Stand, with 210 m hose	
HT15900HRS		Hose Reel & Stand, with 270 m hose	





Hose Lengths:

1 - 30 metres

Hose Reel & Stand:

30 - 270 metres

Maximum Operating Pressure: 1500 bar



▲ Inter-connected with HT-Series hoses Enerpac subsea tensioners apply uniform bolt load.

Model		Hose End 1	Hose End 2	Length
Number				(m)
HT1503		1/4" BSPM	1/4" BSPM	1,0
		120° Cone	120° Cone	
HT1510	-	1/4" BSPM	1/4" BSPM	3,0
		120° Cone	120° Cone	
HT15100	-	1/4" BSPM	1/4" BSPM	30,0
		120° Cone	120° Cone	
HT1503HR *	The Board	BH150	BR150	1,0
HT1506HR *	and the second	BH150	BR150	1,8
HT1510HR *	- B	BH150	BR150	3,0
	- 100 M			
HT1520HR *	The Control	BH150	BR150	6,1
HT15100HR *	and and	BH150	BR150	30,0
HT1503RR *		BR150	BR150	1,0
HT1506RR *	- 30	BR150	BR150	1,8
	7000			
HT1510RR *		BR150	BR150	3,0
	72000			
HT1520RR *		BR150	BR150	6,1

Includes dust caps.

H = Male Nipple (BH-150); R = Female Coupling (BR-150)

1500 BAR COUPLERS				
Description (includes dust caps)		Complete Set	Female Half	Male Half
Quick Disconnect Coupler		B150	BR150	BH150
Quick Disconnect Coupler & Adaptor Kit		BW150AW	-	-
Quick Disconnect Blanking Coupler Set		B150B	BR150B	BH150B

1500 BAR T-PIECES					
Model Number	shown HT15TPMMF	End 1	End 2	End 3	
HT15TPMMF		1x BH150	1x BH150	1x BR150	
HT15TPMMM		1x BH150	1x BH150	1x BH150	

1500 BAR Y-PIPE ASSEMBLIES				
Model Number	shown HT1506YTPMMF	End 1 Hose	End 2 Hose	End 3 T-Piece
HT1506YPMMF	3. 8-1	HT1506HR	HT1506HR	HT15TPMMF
HT1510YPMMF		HT1510HR	HT1510HR	HT15TPMMF
HT1506YPFMF	TO THE WAY OF THE PARTY OF THE	HT1506RR	HT1506RR	HT15TPMMM
HT1510YPFMF	1 2 5	HT1510RR	HT1510RR	НТ15ТРМММ

Y-Pipe Assembly: 1+2= adaptor; 3= stainless steel T with 1/4" BSPM 4= Male Nipple (BH-150); 5= Female Coupling (BR-150); 6= Hose